



Differential Pressure Meter Kit

KANE-DPMKIT

Differential Pressure Meter Kit

Functions

- Pressure range: ± 80 inwg
- Resolution: 0.001" (-9.999 to +9.999 inwg), 0.01" (<-10, >+10 inwg)
- Accuracy: ± 0.03 inwg <3 inwg, $\pm 1\%$ rdg >3 inwg

Features

- High-resolution at ranges below 10 inwg
- Connect to **KANE LIVE™** app
- Or use as a stand-alone manometer
- Easy to Read Backlit Display
- Magnet for Hands Free Use
- Accessory Kit for Static Pressure Tests
- Auto Power Off
- Low Battery Indicator
- Units: bar, mbar, psi, inwg, mmwg, Pa, kPa
- 1-Year limited warranty

Includes

- Stepped T Fitting (2)
- Static Pressure Probe (2)
- Flexible Transparent Tubing (2)
- Brass Fitting (2)
- Step Connector (2)
- Step Connector Tubing (2)
- 60" Pressure Tube
- AAA Batteries (3)
- Soft Case



Free APP

Connects to KANE LIVE™ App on a compatible device



SCAN FOR APP





Wireless Differential Pressure Meter

KANE-DPMKIT

Application

- Test static, gas, and draft pressure

Specifications

Environmental

Measurement range	±80 inwg
Accuracy	±0.03 inwg < 3 inwg, ±1% rdg > 3 inwg
Resolution	0.001 (9.999 to + 9.999 inwg), 0.01" (< -10, > +10 inwg)
Units of measure	bar, mbar, psi, inwg, mmwg, Pa, kPa
Operating Altitude	2000 meters
Humidity	75% max
Operation Temperature	0°C / 32°F to 40°C / 104°F
Storage Temperature	-10°C / 14°F to 50°C / 122°F
Accuracy Temperature	18°C / 64°F to 28°C / 82°F

General

Dimensions	51.0 x 150.5 x 33.4 mm
Weight	180g
Battery	(AAA) x 3
Calibration interval	One year



Made in South Korea